

SIDNEY FR 800



SCHEMA TECNICA

technical data

DESCRIZIONE / DESCRIPTION

Portanza / Load-bearing
ergonomica / ergonomic

Molle / Springs

Molle indipendenti in filo d'acciaio al carbonio fosfatizzato $\varnothing 1,8$ mm, dimensione molla $\varnothing 60$ mm circa, inserite densità molle m^2 300 ca. / Independent springs in carbon-phosphate steel cord $\varnothing 1,8$ mm, spring dimension \varnothing about 60 mm, inserted with a spring density of about 300/ m^2 .

Rinforzo / Reinforcement

Fianchi perimetrali di rinforzo sistema "Box spring" montati sul molleggio in poliuretano espanso ignifugo indeformabile denominato T 30/RC 5E spessore 50 mm e altezza 147 mm ca., densità 30 kg/mc / Reinforced perimeter sides with Box Spring system, assembled on a spring system in flame-resistant crushproof expanded polyurethane called T 30/RC 5E, thickness 50 mm, height about 147 mm, density 30 Kg/ m^3 .

Stabilizzante / Stabiliser

In poliuretano espanso ignifugo indeformabile denominato HT 35 spessore mm 25, densità 35 Kg/mc ad alta resilienza / Flame-resistant crushproof expanded polyurethane called HT 35, thickness 25 mm, density 35 Kg./ m^3 with high resilience.

Imbottitura / Padding

Falda ovatta termolegata ignifuga denominata POLY SLICK HR-FR spessore 30 mm da 500 gr/mq, compostata da ovatta 100% poliestere, trapuntata a losanghe con il tessuto di rivestimento esterno ignifugo e barriera ignifuga denominata TEKNA BARRIERA FR da 140 gr/mq, composta da 90% viscosa e 10% poliestere / Brim in flame-resistant thermo-bonded wadding called POLY SLICK HR-FR, thickness 30 mm, 500 gr/ m^2 , made of wadding 100% polyester, quilted with lozenge shapes, upholstered with a flame-resistant fabric, with a flame-resistant barrier called TEKNA BARRIERA FR, 140 gr/ m^2 , 90% viscose, 10% polyester.

Fascia perimetrale / Perimeter band

In tessuto ignifugo definito KNT 1803/300 STOPFIRE ZONA (100% fibra poliestere FR- peso 240 gr/ m^2) trapuntato con falda di ovatta denominata POLY SLICK HR-FR spessore 8 mm da 200 gr/mq composta da ovatta 100% poliestere e barriera ignifuga denominata TEKNA BARRIERA FR da 140gr/mq, composta da 90% viscosa, 10% poliestere / Made of a flame-resistant fabric called KNT 1803/300 STOPFIRE ZONA (100% polyester fibre FR – weight 240 gr/ m^2), quilted with a wadding brim called POLY SLICK HR-FR, thickness 8 mm, 200 gr/ m^2 , made of wadding 100% polyester, with a flame-resistant barrier called TEKNA BARRIERA FR 140 gr/ m^2 , 90% viscose, 10% polyester.

Rivestimento / Upholstery

Tessuto ignifugo denominato KNT 1803/300 STOPFIRE ZONA (100% fibra poliestere FR- peso 240 gr/ m^2) ricamatura pannello e fissaggio componenti con filo ad alta resistenza / Flame-resistant fabric called KNT 1803/300 STOPFIRE ZONA (100% polyester fibre FR – weight 240 gr/ m^2) – Panel's embroidery and component's fastening with a high-resistance thread.

Altezza / Height

cm 24 ca. / about 24 cm

STRUTTURA / STRUCTURES

