

# MONTREAL FR 800



## SCHEDA TECNICA

technical data

### DESCRIZIONE / DESCRIPTION

**Portanza / Load-bearing**  
ergonomica / ergonomic

**Molle / Springs**

Molle indipendenti in filo d'acciaio al carbonio fosfatizzato Ø 1,8 mm, dimensione molla Ø 60 mm ca., inserite singolarmente in tasche termosaldate realizzate in materiale traspirante. Densità molle m<sup>2</sup> 300 ca. / Independent springs in carbon-phosphate steel cord Ø 1,8 mm, spring dimension Ø about 60 mm, individually inserted in heat-sealed pouches made of breathable material. Spring density about 300/m<sup>2</sup>.

**Rinforzo / Reinforcement**

Fianchi perimetrali di rinforzo sistema "Box Spring" montati sul molleggio in poliuretano espanso ignifugo indeformabile denominato T 30/RC 5E spessore mm 50 e altezza mm 147 ca., densità 30 Kg/mc / Reinforced perimeter sides with Box Spring system, assembled on a spring system in flame-resistant crushproof expanded polyurethane called T 30/RC 5E, thickness 50 mm, height about 147 mm, density 30 Kg/m<sup>3</sup>.

**Stabilizzante / Stabiliser**

In poliuretano espanso ignifugo indeformabile denominato HT 35 spessore mm 25, densità 35 Kg/mc ad alta resilienza / Flame-resistant crushproof expanded polyurethane called HT 35, thickness 25 mm, density 35 Kg/m<sup>3</sup> with high resilience.

**Imbottitura / Padding**

Falda ovatta termolegata ignifuga denominata POLY SLICK HR-FR spessore 30 mm da 500 gr/mq, composta da ovatta 100% poliestere, trapuntata a losanghe con il tessuto di rivestimento esterno Ignifugo e barriera ignifuga denominata TEKNA BARRIERA FR da 140 gr/mq, composta da 90% viscosa, 10% poliestere / Brim in flame-resistant thermo-bonded wadding called POLY SLICK HR-FR, thickness 30 mm, 500 gr/m<sup>2</sup>, made of wadding 100% polyester, quilted with lozenge shapes, upholstered with a flame-resistant fabric, with a flame-resistant barrier called TEKNA BARRIERA FR, 140 gr/m<sup>2</sup>, 90% viscose, 10% polyester.

**Fascia perimetrale / Perimeter band**

In tessuto ignifugo denominato FUEGO 011-00 (61% fibra modacrilica – 39% fibra poliestere – peso 160 gr/m<sup>2</sup>), trapuntato con falda di ovatta denominata POLY SLICK HR-FR spessore 8 mm da 200 gr/mq, composta da ovatta 100% poliestere e barriera ignifuga denominata TEKNA BARRIERA FR da 140 gr/mq, composta da 90% viscosa, 10% poliestere / Made of a flame-resistant fabric called FUEGO 011-00 (61% modacrylic fibre – 39% polyester fibre – weight 160 gr/m<sup>2</sup>), quilted with a wadding brim called POLY SLICK HR-FR, thickness 8 mm, 200 gr/m<sup>2</sup>, made of wadding 100% polyester, with a flame-resistant barrier called TEKNA BARRIERA FR 140 gr/m<sup>2</sup>, 90% viscose, 10% polyester.

**Rivestimento / Upholstery**

Tessuto ignifugo denominato FUEGO 011-00 (61% fibra modacrilica – 39% fibra poliestere – peso 160 gr/m<sup>2</sup>) - Losangatura e fissaggio componenti con filo ad alta resistenza / Flame-resistant fabric called FUEGO 011-00 (61% modacrylic fibre – 39% polyester fibre – weight 160 gr/m<sup>2</sup>) – Lozenge pattern and component's fastening with a high-resistance thread.

**Altezza / Height**

cm 22 ca. / about 22 cm

### STRUTTURA / STRUCTURES

